

Everybody Wants to be Just Like TredMOR®.



Don't be fooled by the imposters,

who changed the color of their product to black and have tried to benefit from the success of TredMOR®.

Be aware, only the real TredMOR®

- ... offers 16 years of successful installations.
- ... has installed millions of square yards.
- ... is made of 100% pure synthetic rubber.
- ... is manufactured to the highest tolerances.
- ... offers Quicklift™ releasable backing which allows for a quick, clean release at the time of removal saving time and labor.
- ... extends carpet life better.
- ... is anti-fatigue.
- ... significantly reduces noise levels.
- ... is of the highest density available.
- ... is moisture resistant.
- ... is inherently anti-microbial/non-allergenic.
- ... is VOC friendly-approved by the CRI.
- ... is the #1 specified carpet cushion in the world.

There's only One TredMOR®

The industry standard since 1985

the REAL TredMor®

Now With
Polytech 360®
Backing
(Not Shown)

from

SCI

SPONGE CUSHION, INC.

P.O. Box 709, 902 Armstrong St.
Morris, IL 60450-0709
Ph: (800) 435-4062 Fax: (800) 423-3357
www.sponge-cushion.com

TYPICAL PRODUCT PROPERTIES

Production Description	Tred-MOR 1562*	Tred-MOR 2568	Tred-MOR 2580	Tred-MOR 2500
<i>Material Content</i>	*Also available to meet Marine USCG Requirements			
Styrene Butadiene Rubber (SBR)	100 % Virgin Enriched SBR Synthetic Rubber	100% Virgin Enriched SBR Synthetic Rubber	100% Virgin Enriched SBR Synthetic Rubber	100% Virgin Enriched SBR Synthetic Rubber
Weight per Sq. Yd.	62 ounces	68 ounces	80 ounces	100 ounces
Thickness	.156 inches	.250 inches	.250 inches	.250 inches
<i>Density</i>	33 lbs. / Cu. Ft.	22 lbs. / Cu. Ft.	26 lbs. / Cu. Ft.	33 lbs. / Cu. Ft.
Facing-Top/Bottom (STD) Underside (Optional) Underside	Non-woven Fiberglass QuikLIFT™ Non-Woven	Non-woven Fiberglass QuikLIFT™ Non-Woven	Non-woven Fiberglass QuikLIFT™ Non-Woven	Non-woven Fiberglass QuikLIFT™ Non-Woven
Width	4' - 6"	4' - 6"	4' - 6"	4' - 6"
Roll Length	60'	60'	60'	60'
Anti-Microbial	Yes	Yes	Yes	Yes
Surface Moisture Resistant	Yes - BlockOUT™	Yes - BlockOUT™	Yes - BlockOUT™	Yes - BlockOUT™
Recommended Use	Extra Heavy Commercial Includes institutional areas subject to CONTINUOUS rolling wheel traffic**.	Heavy Commercial Includes institutional area subject to PERIODIC rolling wheel traffic**.	Extra Heavy Commercial Includes institutional areas subject to FREQUENT rolling wheel traffic**.	Extra Heavy Commercial Includes institutional areas subject to CONTINUOUS rolling wheel traffic**.

**For maximum carpet protection, rolling wheel areas should be double glued to prevent carpet stretching and carpet delamination caused by shear forces and friction.

FLAMMABILITY TESTS

ASTM E 662 (Smoke Chamber)	Pass	Pass	Pass	Pass
FF 1-70 (Pill Test)	Pass	Pass	Pass	Pass
ASTM E 648 (Radiant Panel)	Not applicable to separate carpet cushion. Carpet and cushion must be tested as an assembly.			

EMISSIONS TESTS

CRI Green Label I.D. # CC-973447
Tested and certified by the Carpet & Rug Institute as less than or not exceeding their minimum standards established for total chemical emissions (TVOC) and specific chemicals.

Protocol - University of Pittsburgh S.W.R.I.
Project No. 01-3106-034
Tred-MOR cushion is "No more toxic than wood", the accepted industry standard.

Notes: Scrim backing or other raw materials may be changed without prior notice when shortages occur or when technological advancements become available improving product performance. Typical product properties are derived from averages resulting from usual manufacturing tolerances. Such variances will not affect product quality or performance.

Distributed by:



Block-Out™ hydro-therm vulcanizing seals Tred-MOR's top and bottom surface stopping spills, dirt and moisture penetration. Tracked in snow/water, wet cleaning will not penetrate surface.

Manufactured By:

SCI
Sponge Cushion, Inc.

P.O. Box 709 902 Armstrong St.
Morris, IL 60450-0709
800-435-4062 Fax: 800-423-3557